Lecture 15: Basic Graph Algorithms II

Michael Dinitz

October 14, 2025 601.433/633 Introduction to Algorithms

Introduction


Last time: BFS and DFS

Today: Topological Sort, Strongly Connected Components

▶ Both very classical and important uses of DFS!

Edge Types

DFS naturally gives a spanning forest: edge (v, u) if DFS(v) calls DFS(u)



Forward Edges: (v, u) such that u descendent of v (includes tree edges)

$$start(v) < start(u) < finish(u) < finish(v)$$

Back Edges: (v, u) such that u an ancestor of v start(u) < start(v) < finish(v) < finish(u)


Cross Edges: (v, u) such that u neither a descendent nor an ancestor of v

$$start(u) < finish(u) < start(v) < finish(v)$$

Topological Sort


Definition

A directed graph **G** is a *Directed Acyclic Graph (DAG)* if it has no directed cycles.



Definition

A directed graph **G** is a *Directed Acyclic Graph (DAG)* if it has no directed cycles.




Definition

A topological sort v_1, v_2, \ldots, v_n of a DAG is an ordering of the vertices such that all edges are of the form (v_i, v_j) with i < j.



Definition

A directed graph **G** is a *Directed Acyclic Graph (DAG)* if it has no directed cycles.



Definition

A topological sort v_1, v_2, \ldots, v_n of a DAG is an ordering of the vertices such that all edges are of the form (v_i, v_j) with i < j.



Q: Can we always topological sort a DAG? How fast?

Topological Sort

Algorithm (informal): Run DFS(G). When DFS(v) returns, put v at beginning of list

Topological Sort

Algorithm (informal): Run DFS(G). When DFS(v) returns, put v at beginning of list

```
DFS(G) {
   list → head = NULL
   t=0:
   for all \mathbf{v} \in \mathbf{V} {
       start(v) = 0:
       finish(v) = 0;
   while \exists v \in V with start(v) = 0 {
       DFS(v):
```

```
DFS(v) {
   t = t + 1:
   start(v) = t;
   for each edge (v, u) \in A[v] {
       if start(u) == 0 then DFS(u);
   t = t + 1:
   finish(v) = t:
   temp = list \rightarrow head
   list \rightarrow head = v
   list \rightarrow head \rightarrow next = temp
```

Theorem

A directed graph G is a DAG if and only if DFS(G) has no back edges.

Theorem

A directed graph G is a DAG if and only if DFS(G) has no back edges.

Proof.

Only if (\Rightarrow) : contrapositive. If G has a back edge:

Theorem

A directed graph G is a DAG if and only if DFS(G) has no back edges.

Proof.

Only if (\Rightarrow) : contrapositive. If G has a back edge: Directed cycle! Not a DAG.

Theorem

A directed graph G is a DAG if and only if DFS(G) has no back edges.

Proof.

Only if (\Rightarrow) : contrapositive. If G has a back edge: Directed cycle! Not a DAG.

If (\Leftarrow) : contrapositive. If G has a directed cycle C:

Theorem

A directed graph G is a DAG if and only if DFS(G) has no back edges.

Proof.

Only if (\Rightarrow) : contrapositive. If G has a back edge: Directed cycle! Not a DAG.

If (\Leftarrow) : contrapositive. If G has a directed cycle C:

- Let $u \in C$ with minimum start value, v predecessor in cycle
- lacktriangle All nodes in $m{C}$ reachable from $m{u} \implies$ all nodes in $m{C}$ descendants of $m{u}$
- (v, u) a back edge



Correctness:

Correctness: Since \boldsymbol{G} a DAG, never see back edge

Correctness: Since G a DAG, never see back edge

 \implies Every edge (\mathbf{v}, \mathbf{u}) out of \mathbf{v} a forward or cross edge

 \implies finish(u) < finish(v)

 \implies u already in list when v added to beginning

Correctness: Since G a DAG, never see back edge

- \implies Every edge (v, u) out of v a forward or cross edge
- \implies finish(u) < finish(v)
- \implies **u** already in list when **v** added to beginning

Running Time:

Correctness: Since G a DAG, never see back edge

 \implies Every edge (v, u) out of v a forward or cross edge

 \implies finish(u) < finish(v)

 \implies **u** already in list when **v** added to beginning

Running Time: Same as DFS! O(m+n)

Strongly Connected Components (SCC)

Another application of DFS. "Kosaraju's Algorithm": Developed by Rao Kosaraju, professor emeritus at JHU CS!

G = (V, E) a directed graph.

Definition


 $C \subseteq V$ is a strongly connected component (SCC) if it is a maximal subset such that for all $u, v \in C$, u can reach v and vice versa (bireachable).

Another application of DFS. "Kosaraju's Algorithm": Developed by Rao Kosaraju, professor emeritus at JHU CS!

G = (V, E) a directed graph.

Definition

 $C \subseteq V$ is a strongly connected component (SCC) if it is a maximal subset such that for all $u, v \in C$, u can reach v and vice versa (bireachable).




Another application of DFS. "Kosaraju's Algorithm": Developed by Rao Kosaraju, professor emeritus at JHU CS!

G = (V, E) a directed graph.

Definition

 $C \subseteq V$ is a strongly connected component (SCC) if it is a maximal subset such that for all $u, v \in C$, u can reach v and vice versa (bireachable).




Fact: There is a *unique* partition of \boldsymbol{V} into SCCs

Another application of DFS. "Kosaraju's Algorithm": Developed by Rao Kosaraju, professor emeritus at JHU CS!

G = (V, E) a directed graph.

Definition

 $C \subseteq V$ is a strongly connected component (SCC) if it is a maximal subset such that for all $u, v \in C$, u can reach v and vice versa (bireachable).



Fact: There is a *unique* partition of **V** into SCCs

Proof: Bireachability is an equivalence relation: if \boldsymbol{u} and \boldsymbol{v} are bireachable, and \boldsymbol{v} and \boldsymbol{w} are bireachable, then \boldsymbol{u} and \boldsymbol{w} are bireachable

Problem: Given \boldsymbol{G} , compute SCCs (partition \boldsymbol{V} into the SCCs)

Problem: Given G, compute SCCs (partition V into the SCCs)

Trivial Algorithm:

Problem: Given \boldsymbol{G} , compute SCCs (partition \boldsymbol{V} into the SCCs)

Trivial Algorithm: DFS/BFS from every node, keep track of what's reachable from where

Problem: Given **G**, compute SCCs (partition **V** into the SCCs)

Trivial Algorithm: DFS/BFS from every node, keep track of what's reachable from where

▶ Running time: O(n(m+n))

Problem: Given **G**, compute SCCs (partition **V** into the SCCs)

Trivial Algorithm: DFS/BFS from every node, keep track of what's reachable from where

▶ Running time: O(n(m+n))

Can we do better? O(m+n)?

Graph of SCCs


Definition: Let \hat{G} be graph of SCCs:

- ▶ Vertex **v(C)** for each SCC **C**
- ▶ Edge (v(C), v(C')) if $\exists u \in C, v \in C'$ such that $(u, v) \in E$

Graph of SCCs

Definition: Let \hat{G} be graph of SCCs:

- ▶ Vertex v(C) for each SCC C
- ▶ Edge (v(C), v(C')) if $\exists u \in C, v \in C'$ such that $(u, v) \in E$



Theorem


 $\hat{\boldsymbol{G}}$ is a DAG.

Theorem

 $\hat{\boldsymbol{G}}$ is a DAG.

Proof.

Suppose $\hat{\mathbf{G}}$ not a DAG. Then there is a directed cycle \mathbf{H} .




Theorem

 $\hat{\boldsymbol{G}}$ is a DAG.

Proof.

Suppose $\hat{\boldsymbol{G}}$ not a DAG. Then there is a directed cycle \boldsymbol{H} .

 $\Longrightarrow \bigcup_{C:\nu(C)\in H} C$ is an SCC



Theorem


 $\hat{\boldsymbol{G}}$ is a DAG.

Proof.

Suppose $\hat{\boldsymbol{G}}$ not a DAG. Then there is a directed cycle \boldsymbol{H} .

 $\Longrightarrow \bigcup_{C:v(C)\in H} C$ is an SCC

 $\implies \nu(C)$ not an SCC for $\nu(C) \in H$



Theorem

 $\hat{\boldsymbol{G}}$ is a DAG.


Proof.

Suppose $\hat{\boldsymbol{G}}$ not a DAG. Then there is a directed cycle \boldsymbol{H} .

 $\Longrightarrow \bigcup_{C:v(C)\in H} C$ is an SCC

 $\implies v(C)$ not an SCC for $v(C) \in H$

Contradiction!



Since $\hat{\boldsymbol{G}}$ a DAG, has a topological sort



Since $\hat{\boldsymbol{G}}$ a DAG, has a topological sort



Definition: SCC *C* is a *sink* SCC if no outgoing edges, *source* SCC if no incoming edges

Claim: At least one sink SCC exists

Since $\hat{\boldsymbol{G}}$ a DAG, has a topological sort



Definition: SCC *C* is a *sink* SCC if no outgoing edges, *source* SCC if no incoming edges

- Claim: At least one sink SCC exists
- Proof: Final SCC in topological sort of \hat{G} must be a sink.

Since $\hat{\boldsymbol{G}}$ a DAG, has a topological sort



Definition: SCC *C* is a *sink* SCC if no outgoing edges, *source* SCC if no incoming edges

- Claim: At least one sink SCC exists
- Proof: Final SCC in topological sort of $\hat{\mathbf{G}}$ must be a sink.

What happens if we run DFS(ν) where ν in a sink SCC?

Since $\hat{\boldsymbol{G}}$ a DAG, has a topological sort



Definition: SCC *C* is a *sink* SCC if no outgoing edges, *source* SCC if no incoming edges

- Claim: At least one sink SCC exists
- Proof: Final SCC in topological sort of $\hat{\mathbf{G}}$ must be a sink.

What happens if we run DFS(ν) where ν in a sink SCC?

▶ See exactly nodes in *C*!

Since $\hat{\boldsymbol{G}}$ a DAG, has a topological sort



Definition: SCC *C* is a *sink* SCC if no outgoing edges, *source* SCC if no incoming edges

- Claim: At least one sink SCC exists
- Proof: Final SCC in topological sort of \hat{G} must be a sink.

What happens if we run DFS(ν) where ν in a sink SCC?

► See exactly nodes in *C*!

Strategy: find node in sink SCC, run DFS, remove nodes found, repeat

Run DFS(G), and let $finish(C) = \max_{v \in C} finish(v)$

Lemma


Let C_1 , C_2 distinct SCCs s.t. $(v(C_1), v(C_2)) \in E(\hat{G})$. Then $finish(C_1) > finish(C_2)$.

Run DFS(G), and let $finish(C) = \max_{v \in C} finish(v)$

Lemma

Let C_1 , C_2 distinct SCCs s.t. $(v(C_1), v(C_2)) \in E(\hat{G})$. Then $finish(C_1) > finish(C_2)$.

Proof.




Let $x \in C_1 \cup C_2$ be first node encountered by DFS

Run DFS(G), and let $finish(C) = \max_{v \in C} finish(v)$

Lemma

Let C_1 , C_2 distinct SCCs s.t. $(v(C_1), v(C_2)) \in E(\hat{G})$. Then $finish(C_1) > finish(C_2)$.

Proof.



Let $x \in C_1 \cup C_2$ be first node encountered by DFS


▶ If *x* ∈ *C*₁:

Run DFS(G), and let $finish(C) = \max_{v \in C} finish(v)$

Lemma

Let C_1 , C_2 distinct SCCs s.t. $(v(C_1), v(C_2)) \in E(\hat{G})$. Then $finish(C_1) > finish(C_2)$.

Proof.



Let $x \in C_1 \cup C_2$ be first node encountered by DFS


If $x \in C_1$: all of C_2 reachable from x, so DFS(x) does not complete until all of C_2 finished

Run DFS(G), and let $finish(C) = \max_{v \in C} finish(v)$

Lemma

Let C_1 , C_2 distinct SCCs s.t. $(v(C_1), v(C_2)) \in E(\hat{G})$. Then $finish(C_1) > finish(C_2)$.

Proof.



Let $x \in C_1 \cup C_2$ be first node encountered by DFS


- If $x \in C_1$: all of C_2 reachable from x, so DFS(x) does not complete until all of C_2 finished
- **▶** If *x* ∈ *C*₂:

Run DFS(G), and let $finish(C) = \max_{v \in C} finish(v)$

Lemma

Let C_1 , C_2 distinct SCCs s.t. $(v(C_1), v(C_2)) \in E(\hat{G})$. Then $finish(C_1) > finish(C_2)$.

Proof.



Let $x \in C_1 \cup C_2$ be first node encountered by DFS


- If $x \in C_1$: all of C_2 reachable from x, so DFS(x) does not complete until all of C_2 finished
- If $x \in C_2$: all of C_2 reachable from x but nothing from C_1 , so all of C_2 finishes before any node in C_1 starts

Run DFS(G), and let $finish(C) = \max_{v \in C} finish(v)$

Lemma

Let C_1, C_2 distinct SCCs s.t. $(v(C_1), v(C_2)) \in E(\hat{G})$. Then $finish(C_1) > finish(C_2)$.

Proof.



Let $x \in C_1 \cup C_2$ be first node encountered by DFS

- If $x \in C_1$: all of C_2 reachable from x, so DFS(x) does not complete until all of C_2 finished
- ▶ If $x \in C_2$: all of C_2 reachable from x but nothing from C_1 , so all of C_2 finishes before any node in C_1 starts

So node of max finishing time in a source SCC (no incoming edges in $\hat{\boldsymbol{G}}$).

Run DFS(G) to get finish times.

Corollary

Let \mathcal{C} be collection of all SCCs of G, and let $\mathcal{C}' \subseteq C$. Let $G' = G \setminus (\bigcup_{C \in \mathcal{C}'} C)$. Then the node $\mathbf{v} = \operatorname{argmax}_{\mathbf{u} \in \bigcup_{C \in \mathcal{C} \setminus C'}} \mathbf{c}$ finish (\mathbf{u}) is in an SCC of G that is a source SCC of G'.

Run DFS(G) to get finish times.

Corollary

Let \mathcal{C} be collection of all SCCs of G, and let $\mathcal{C}' \subseteq C$. Let $G' = G \setminus (\bigcup_{C \in \mathcal{C}'} C)$. Then the node $\mathbf{v} = \underset{\mathbf{u} \in \bigcup_{C \in \mathcal{C} \setminus C'}}{\mathbf{c}} finish(\mathbf{u})$ is in an SCC of G that is a source SCC of G'.

Proof Sketch.

Clearly SCCs of G' are precisely $C \setminus C'$:



Run DFS(G) to get finish times.

Corollary

Let \mathcal{C} be collection of all SCCs of G, and let $\mathcal{C}' \subseteq C$. Let $G' = G \setminus (\bigcup_{C \in \mathcal{C}'} C)$. Then the node $\mathbf{v} = \underset{\mathbf{u} \in \bigcup_{C \in \mathcal{C} \setminus \mathcal{C}'} C}{\mathsf{finish}}(\mathbf{u})$ is in an SCC of G that is a source SCC of G'.

Proof Sketch.

Clearly SCCs of G' are precisely $C \setminus C'$:



Suppose \mathbf{v} in SCC \mathbf{C} not source SCC of \mathbf{G}'

Run DFS(G) to get finish times.

Corollary

Let \mathcal{C} be collection of all SCCs of G, and let $\mathcal{C}' \subseteq C$. Let $G' = G \setminus (\bigcup_{C \in \mathcal{C}'} C)$. Then the node $\mathbf{v} = \underset{\mathbf{u} \in \bigcup_{C \in \mathcal{C} \setminus C'}}{\operatorname{cfinish}}(\mathbf{u})$ is in an SCC of G that is a source SCC of G'.

Proof Sketch.

Clearly SCCs of G' are precisely $C \setminus C'$:



Suppose \mathbf{v} in SCC \mathbf{C} not source SCC of \mathbf{G}'

 \implies exists edge (u', v') in G' where $v' \in C$ but u' in different SCC C'

Run DFS(G) to get finish times.

Corollary

Let \mathcal{C} be collection of all SCCs of G, and let $\mathcal{C}' \subseteq C$. Let $G' = G \setminus (\bigcup_{C \in \mathcal{C}'} C)$. Then the node $\mathbf{v} = \underset{\mathbf{u} \in \bigcup_{C \in \mathcal{C}'} C}{\operatorname{const}} (\mathbf{c} \underset{\mathbf{c}}{\operatorname{finish}}(\mathbf{u})$ is in an SCC of G that is a source SCC of G'.

Proof Sketch.

Clearly SCCs of G' are precisely $C \setminus C'$:



Suppose \mathbf{v} in SCC \mathbf{C} not source SCC of \mathbf{G}'

 \implies exists edge (u', v') in G' where $v' \in C$ but u' in different SCC C'

Lemma \implies finish(C') > finish(C), contradiction to def of ν .

So node with max finish time in a *source* SCC (no incoming edges in $\hat{\mathbf{G}}$). Want sink (no outgoing edges).

So node with max finish time in a *source* SCC (no incoming edges in $\hat{\mathbf{G}}$). Want sink (no outgoing edges). Reverse all edges!

So node with max finish time in a *source* SCC (no incoming edges in $\hat{\mathbf{G}}$). Want sink (no outgoing edges). Reverse all edges!

Definition: G^T is G with all edges reversed.

• Source SCC in G^T is sink SCC in G

So node with max finish time in a *source* SCC (no incoming edges in $\hat{\mathbf{G}}$). Want sink (no outgoing edges). Reverse all edges!

Definition: G^T is G with all edges reversed.

• Source SCC in G^T is sink SCC in G

Kosaraju's Algorithm:

- ▶ DFS(G^T) to get finishing times and order π on V from largest finishing time to smallest
- ▶ Set mark(v) = False for all $v \in V$
- Forall **v** ∈ **V** in order of π {
 if **mark(v)** = **False** {
 Run DFS(**v**), let **C** be all nodes found
 Return **C** as an SCC
 }

So node with max finish time in a *source* SCC (no incoming edges in $\hat{\mathbf{G}}$). Want sink (no outgoing edges). Reverse all edges!

Definition: G^T is G with all edges reversed.

• Source SCC in G^T is sink SCC in G

Kosaraju's Algorithm:

- ▶ DFS(G^T) to get finishing times and order π on V from largest finishing time to smallest
- ▶ Set mark(v) = False for all $v \in V$

```
Forall v ∈ V in order of π {
if mark(v) = False {
Run DFS(v), let C be all nodes found
Return C as an SCC
}
```

Running Time:

So node with max finish time in a *source* SCC (no incoming edges in $\hat{\mathbf{G}}$). Want sink (no outgoing edges). Reverse all edges!

Definition: G^T is G with all edges reversed.

• Source SCC in G^T is sink SCC in G

Kosaraju's Algorithm:

- ▶ DFS(G^T) to get finishing times and order π on V from largest finishing time to smallest
- ▶ Set mark(v) = False for all $v \in V$

```
    Forall v ∈ V in order of π {
        if mark(v) = False {
            Run DFS(v), let C be all nodes found
            Return C as an SCC
        }
```

Running Time: O(m+n)

Let C_1, C_2, \dots, C_k be sets identified by algorithm (in order)

Theorem

 C_i is a sink SCC of $G \setminus \left(\bigcup_{j=1}^{i-1} C_j\right)$, and an SCC of G.

Let C_1, C_2, \ldots, C_k be sets identified by algorithm (in order)

Theorem

 C_i is a sink SCC of $G \setminus \left(\bigcup_{j=1}^{i-1} C_j\right)$, and an SCC of G.

Proof Sketch.

Induction on i.



Let C_1, C_2, \ldots, C_k be sets identified by algorithm (in order)

Theorem

 C_i is a sink SCC of $G \setminus \left(\bigcup_{j=1}^{i-1} C_j\right)$, and an SCC of G.

Proof Sketch.

Induction on i.

Base case: i = 1. By previous lemma, largest finishing time in $G^T \implies$ in sink SCC of G

 \implies C_1 is sink SCC of G

Let C_1, C_2, \ldots, C_k be sets identified by algorithm (in order)

Theorem

 C_i is a sink SCC of $G \setminus \left(\bigcup_{i=1}^{i-1} C_i\right)$, and an SCC of G.

Proof Sketch.

Induction on *i*.

Base case: i = 1. By previous lemma, largest finishing time in $G^T \implies$ in sink SCC of G $\implies C_1$ is sink SCC of G

Inductive case: Let i > 1. Let v unmarked node with largest finishing time.

- ▶ By induction, subgraph of unmarked nodes is G minus i-1 SCCs of G
- ► Corollary ⇒ v must be in sink SCC of unmarked nodes so get an SCC of unmarked nodes when run DES
- ▶ Corollary ⇒ SCC of original graph