### Lecture 17: All-Pairs Shortest Paths

Jessica Sorrell

October 28, 2025 601.433/633 Introduction to Algorithms Slides by Michael Dinitz

### Announcements

- Mid-Semester feedback on Courselore!
- No lecture notes

### Setup:

- ▶ Directed graph G = (V, E)
- ▶ Length  $\ell(x,y)$  on each edge  $(x,y) \in E$
- ▶ Length of path P is  $\ell(P) = \sum_{(x,y) \in P} \ell(x,y)$
- $d(x,y) = \min_{x \to y \text{ paths } P} \ell(P)$

Last time: All distances from source node  $\mathbf{v} \in \mathbf{V}$ .

Today: Distances between all pairs of nodes!

### Setup:

- ▶ Directed graph G = (V, E)
- ▶ Length  $\ell(x,y)$  on each edge  $(x,y) \in E$
- ▶ Length of path P is  $\ell(P) = \sum_{(x,y) \in P} \ell(x,y)$
- $d(x,y) = \min_{x \to y \text{ paths } P} \ell(P)$

Last time: All distances from source node  $\mathbf{v} \in \mathbf{V}$ .

Today: Distances between all pairs of nodes!

Obvious solution:

### Setup:

- ▶ Directed graph G = (V, E)
- ▶ Length  $\ell(x,y)$  on each edge  $(x,y) \in E$
- ▶ Length of path P is  $\ell(P) = \sum_{(x,y) \in P} \ell(x,y)$
- $d(x,y) = \min_{x \to y \text{ paths } P} \ell(P)$

Last time: All distances from source node  $\mathbf{v} \in \mathbf{V}$ .

Today: Distances between all pairs of nodes!

Obvious solution: single-source from each  $v \in V$ 

### Setup:

- Directed graph G = (V, E)
- ▶ Length  $\ell(x,y)$  on each edge  $(x,y) \in E$
- ▶ Length of path P is  $\ell(P) = \sum_{(x,y) \in P} \ell(x,y)$
- $d(x,y) = \min_{x \to y \text{ paths } P} \ell(P)$

Last time: All distances from source node  $\mathbf{v} \in \mathbf{V}$ .

Today: Distances between all pairs of nodes!

Obvious solution: single-source from each  $v \in V$ 

- ▶ No negative weights: n runs of Dijkstra, time  $O(n(m + n \log n))$
- Negative weights: n runs of Bellman-Ford, time  $O(nmn) = O(mn^2)$

### Setup:

- ▶ Directed graph G = (V, E)
- ▶ Length  $\ell(x,y)$  on each edge  $(x,y) \in E$
- ▶ Length of path **P** is  $\ell(P) = \sum_{(x,y) \in P} \ell(x,y)$
- $d(x,y) = \min_{x \to y \text{ paths } P} \ell(P)$

Last time: All distances from source node  $\mathbf{v} \in \mathbf{V}$ .

Today: Distances between all pairs of nodes!

Obvious solution: single-source from each  $\mathbf{v} \in \mathbf{V}$ 

- ▶ No negative weights: n runs of Dijkstra, time  $O(n(m + n \log n))$
- ▶ Negative weights: n runs of Bellman-Ford, time  $O(nmn) = O(mn^2)$

Can we do better? Particularly for negative edge weights?

▶ Main goal today: Negative weights as fast as possible.

Jessica Sorrell Lecture 17: APSP October 28, 2025

3 / 14

# Floyd-Warshall: A Different Dynamic Programming Approach

To simplify notation, let  $V = \{1, 2, \dots, n\}$  and  $\ell(i, j) = \infty$  if  $(i, j) \notin E$ 

Bellman-Ford subproblems: length of shortest path with at most some number of edges

Jessica Sorrell Lecture 17: APSP October 28, 2025 5/14

## Floyd-Warshall: A Different Dynamic Programming Approach

To simplify notation, let  $V = \{1, 2, \dots, n\}$  and  $\ell(i, j) = \infty$  if  $(i, j) \notin E$ 

Bellman-Ford subproblems: length of shortest path with at most some number of edges

### New subproblems:

- Intuition: "shortest path from u to v either goes through node n, or it doesn't"
  - ▶ If it doesn't: shortest uses only first nodes in  $\{1, 2, ..., n-1\}$ .
  - If it does: consists of a path  $P_1$  from u to n and a path  $P_2$  from n to v, neither of which uses n (internally).

Jessica Sorrell Lecture 17: APSP October 28, 2025 5 / 14

## Floyd-Warshall: A Different Dynamic Programming Approach

To simplify notation, let  $V = \{1, 2, ..., n\}$  and  $\ell(i, j) = \infty$  if  $(i, j) \notin E$ 

Bellman-Ford subproblems: length of shortest path with at most some number of edges

### New subproblems:

- Intuition: "shortest path from u to v either goes through node n, or it doesn't"
  - If it doesn't: shortest uses only first nodes in  $\{1, 2, ..., n-1\}$ .
  - If it does: consists of a path  $P_1$  from u to n and a path  $P_2$  from n to v, neither of which uses **n** (internally).
- ▶ Subproblems: shortest path from u to v that only uses nodes in  $\{1,2,\ldots k\}$  for all u, v, k

Jessica Sorrell Lecture 17: APSP 5 / 14 October 28, 2025

 $u \rightarrow v$  path **P**: "intermediate nodes" are all nodes in **P** other than u, v.

- ▶ Goal: compute  $d_{ii}^k$  for all  $i, j, k \in [n]$ .
- ▶ Return  $d_{ii}^n$  for all  $i, j \in V$ .

 $u \rightarrow v$  path **P**: "intermediate nodes" are all nodes in **P** other than u, v.

- ▶ Goal: compute  $d_{ij}^k$  for all  $i, j, k \in [n]$ .
- ▶ Return  $d_{ii}^n$  for all  $i, j \in V$ .

$$d_{ij}^{k} = \begin{cases} & \text{if } k = 0 \\ & \text{if } k \ge 1 \end{cases}$$

 $u \rightarrow v$  path **P**: "intermediate nodes" are all nodes in **P** other than u, v.

- ▶ Goal: compute  $d_{ii}^k$  for all  $i, j, k \in [n]$ .
- ▶ Return  $d_{ii}^n$  for all  $i, j \in V$ .

$$d_{ij}^{k} = \begin{cases} \ell(i,j) & \text{if } k = 0 \\ & \text{if } k \ge 1 \end{cases}$$

 $u \rightarrow v$  path **P**: "intermediate nodes" are all nodes in **P** other than u, v.

- ▶ Goal: compute  $d_{ii}^k$  for all  $i, j, k \in [n]$ .
- ▶ Return  $d_{ii}^n$  for all  $i, j \in V$ .

$$d_{ij}^{k} = \begin{cases} \ell(i,j) & \text{if } k = 0\\ \min(d_{ij}^{k-1}, d_{ik}^{k-1} + d_{kj}^{k-1}) & \text{if } k \geq 1 \end{cases}$$

### Theorem

For all  $i, j, k \in [n]$ :

$$d_{ij}^{k} = \begin{cases} \ell(i,j) & \text{if } k = 0\\ \min(d_{ij}^{k-1}, d_{ik}^{k-1} + d_{kj}^{k-1}) & \text{if } k \ge 1 \end{cases}$$

### Theorem

For all  $i, j, k \in [n]$ :

$$d_{ij}^{k} = \begin{cases} \ell(i,j) & \text{if } k = 0\\ \min(d_{ij}^{k-1}, d_{ik}^{k-1} + d_{kj}^{k-1}) & \text{if } k \ge 1 \end{cases}$$

If 
$$k = 0$$
:  $\checkmark$ 

#### Theorem

For all  $i, j, k \in [n]$ :

$$d_{ij}^{k} = \begin{cases} \ell(i,j) & \text{if } k = 0\\ \min(d_{ij}^{k-1}, d_{ik}^{k-1} + d_{kj}^{k-1}) & \text{if } k \ge 1 \end{cases}$$

If k = 0:  $\checkmark$ 

If  $k \ge 1$ : prove  $\le$  and  $\ge$ 

### Theorem

For all  $i, j, k \in [n]$ :

$$d_{ij}^{k} = \begin{cases} \ell(i,j) & \text{if } k = 0\\ \min(d_{ij}^{k-1}, d_{ik}^{k-1} + d_{kj}^{k-1}) & \text{if } k \ge 1 \end{cases}$$

If k = 0:  $\checkmark$ 

If  $k \ge 1$ : prove  $\le$  and  $\ge$ 

≤:

#### Theorem

For all  $i, j, k \in [n]$ :

$$d_{ij}^{k} = \begin{cases} \ell(i,j) & \text{if } k = 0\\ \min(d_{ij}^{k-1}, d_{ik}^{k-1} + d_{kj}^{k-1}) & \text{if } k \ge 1 \end{cases}$$

If k = 0:  $\checkmark$ 

If  $k \ge 1$ : prove  $\le$  and  $\ge$ 

≤: Two feasible solutions

#### Theorem

For all  $i, j, k \in [n]$ :

$$d_{ij}^{k} = \begin{cases} \ell(i,j) & \text{if } k = 0\\ \min(d_{ij}^{k-1}, d_{ik}^{k-1} + d_{kj}^{k-1}) & \text{if } k \ge 1 \end{cases}$$

If k = 0:  $\checkmark$ 

If  $k \ge 1$ : prove  $\le$  and  $\ge$ 

≤: Two feasible solutions

 $\geq$ : Let **P** be shortest  $i \rightarrow j$  path with all intermediate nodes in [k]

▶ If **k** not an intermediate node of **P**:

#### Theorem

For all  $i, j, k \in [n]$ :

$$d_{ij}^{k} = \begin{cases} \ell(i,j) & \text{if } k = 0\\ \min(d_{ij}^{k-1}, d_{ik}^{k-1} + d_{kj}^{k-1}) & \text{if } k \ge 1 \end{cases}$$

If k = 0:  $\checkmark$ 

If  $k \geq 1$ : prove  $\leq$  and  $\geq$ 

<: Two feasible solutions

 $\geq$ : Let **P** be shortest  $i \rightarrow j$  path with all intermediate nodes in [k]

If k not an intermediate node of P: P has all intermediate nodes in  $[k-1] \implies$  $\min(d_{ii}^{k-1}, d_{ik}^{k-1} + d_{ki}^{k-1}) \le d_{ii}^{k-1} \le \ell(P) = d_{ii}^{k}$ 

Lecture 17: APSP October 28, 2025 7 / 14

#### Theorem

For all  $i, j, k \in [n]$ :

$$d_{ij}^{k} = \begin{cases} \ell(i,j) & \text{if } k = 0\\ \min(d_{ij}^{k-1}, d_{ik}^{k-1} + d_{kj}^{k-1}) & \text{if } k \ge 1 \end{cases}$$

If k = 0:  $\checkmark$ 

If  $k \ge 1$ : prove  $\le$  and  $\ge$ 

≤: Two feasible solutions

 $\geq$ : Let **P** be shortest  $i \rightarrow j$  path with all intermediate nodes in [k]

- If k not an intermediate node of P: P has all intermediate nodes in  $[k-1] \implies \min(d_{ii}^{k-1}, d_{ik}^{k-1} + d_{ki}^{k-1}) \le d_{ii}^{k-1} \le \ell(P) = d_{ii}^k$
- ▶ If **k** is an intermediate node of **P**:

#### Theorem

For all  $i, j, k \in [n]$ :

$$d_{ij}^{k} = \begin{cases} \ell(i,j) & \text{if } k = 0\\ \min(d_{ij}^{k-1}, d_{ik}^{k-1} + d_{kj}^{k-1}) & \text{if } k \ge 1 \end{cases}$$

If k = 0:  $\checkmark$ 

If  $k \ge 1$ : prove  $\le$  and  $\ge$ 

≤: Two feasible solutions

 $\geq$ : Let **P** be shortest  $i \rightarrow j$  path with all intermediate nodes in [k]

- If k not an intermediate node of P: P has all intermediate nodes in  $[k-1] \implies \min(d_{ii}^{k-1}, d_{ik}^{k-1} + d_{ki}^{k-1}) \le d_{ii}^{k-1} \le \ell(P) = d_{ii}^{k}$
- If k is an intermediate node of P: divide P into  $P_1$  (subpath from i to k) and  $P_2$  (subpath from k to j)

$$\min(d_{ij}^{k-1},d_{ik}^{k-1}+d_{kj}^{k-1}) \leq d_{ik}^{k-1}+d_{kj}^{k-1} \leq \ell(P_1)+\ell(P_2)=\ell(P)=d_{ij}^k$$

Usually bottom-up, since so simple:

```
M[i,j,0] = \ell(i,j) for all i,j \in [n] for (k=1 \text{ to } n) for (i=1 \text{ to } n) for (j=1 \text{ to } n) M[i,j,k] = \min(M[i,j,k-1],M[i,k,k-1]+M[k,j,k-1])
```

Usually bottom-up, since so simple:

```
M[i,j,0] = \ell(i,j) for all i,j \in [n]
for (k=1 \text{ to } n)
for (i=1 \text{ to } n)
for (j=1 \text{ to } n)
M[i,j,k] = \min(M[i,j,k-1], M[i,k,k-1] + M[k,j,k-1])
```

**Correctness:** obvious for k = 0. For  $k \ge 1$ :

$$\begin{aligned} M[i,j,k] &= \min(M[i,j,k-1], M[i,k,k-1] + M[k,j,k-1]) \\ &= \min(d_{ij}^{k-1}, d_{ik}^{k-1} + d_{kj}^{k-1}) \end{aligned} \qquad \text{(def of algorithm)} \\ &= d_{ii}^{k} \qquad \text{(optimal substructure)} \end{aligned}$$

Usually bottom-up, since so simple:

```
M[i,j,0] = \ell(i,j) for all i,j \in [n]
for (k=1 \text{ to } n)
for (i=1 \text{ to } n)
for (j=1 \text{ to } n)
M[i,j,k] = \min(M[i,j,k-1], M[i,k,k-1] + M[k,j,k-1])
```

**Correctness:** obvious for k = 0. For  $k \ge 1$ :

$$\begin{split} M[i,j,k] &= \min(M[i,j,k-1], M[i,k,k-1] + M[k,j,k-1]) & \text{(def of algorithm)} \\ &= \min(d_{ij}^{k-1}, d_{ik}^{k-1} + d_{kj}^{k-1}) & \text{(induction)} \\ &= d_{ij}^{k} & \text{(optimal substructure)} \end{split}$$

Running Time:  $O(n^3)$ 

### Fun Fact



Search... Help | Adva

#### Computer Science > Data Structures and Algorithms

[Submitted on 2 Apr 2019]

# Incorrect implementations of the Floyd--Warshall algorithm give correct solutions after three repeats

Ikumi Hide, Soh Kumabe, Takanori Maehara

The Floyd--Warshall algorithm is a well-known algorithm for the all-pairs shortest path problem that is simply implemented by triply nested loops. In this study, we show that the incorrect implementations of the Floyd--Warshall algorithm that misorder the triply nested loops give correct solutions if these are repeated three times.

Subjects: Data Structures and Algorithms (cs.DS)

Cite as: arXiv:1904.01210 [cs.DS]

(or arXiv:1904.01210v1 [cs.DS] for this version)

https://doi.org/10.48550/arXiv.1904.01210

#### **Submission history**

From: Takanori Maehara [view email] [v1] Tue, 2 Apr 2019 04:39:28 UTC (4 KB)

Johnson's Algorithm

Different Approach: Can we "fix" negative weights so Dijkstra from every node works?

► Time would be  $O(n(m + n \log n)) = O(mn + n^2 \log n)$ , better than Floyd-Warshall

Different Approach: Can we "fix" negative weights so Dijkstra from every node works?

▶ Time would be  $O(n(m + n \log n)) = O(mn + n^2 \log n)$ , better than Floyd-Warshall

First attempt: Let  $-\alpha$  be smallest length (most negative). Add  $\alpha$  to every edge.

Does this work?

Different Approach: Can we "fix" negative weights so Dijkstra from every node works?

▶ Time would be  $O(n(m + n \log n)) = O(mn + n^2 \log n)$ , better than Floyd-Warshall

First attempt: Let  $-\alpha$  be smallest length (most negative). Add  $\alpha$  to every edge.

Does this work? No!

Different Approach: Can we "fix" negative weights so Dijkstra from every node works?

Time would be  $O(n(m + n \log n)) = O(mn + n^2 \log n)$ , better than Floyd-Warshall

First attempt: Let  $-\alpha$  be smallest length (most negative). Add  $\alpha$  to every edge.

- Does this work? No!
- New length of path P is  $\ell(P) + \alpha |P|$ , so original shortest path might no longer be shortest path if it has many edges.



Different Approach: Can we "fix" negative weights so Dijkstra from every node works?

► Time would be  $O(n(m + n \log n)) = O(mn + n^2 \log n)$ , better than Floyd-Warshall

First attempt: Let  $-\alpha$  be smallest length (most negative). Add  $\alpha$  to every edge.

- Does this work? No!
- New length of path P is  $\ell(P) + \alpha |P|$ , so original shortest path might no longer be shortest path if it has many edges.

200 300 100 (01 1-1 (01 101)

Some other kind of reweighting? Need new lengths  $\hat{\ell}$  such that:

Jessica Sorrell Lecture 17: APSP October 28, 2025 11 / 14

Different Approach: Can we "fix" negative weights so Dijkstra from every node works?

▶ Time would be  $O(n(m + n \log n)) = O(mn + n^2 \log n)$ , better than Floyd-Warshall

First attempt: Let  $-\alpha$  be smallest length (most negative). Add  $\alpha$  to every edge.

- Does this work? No!
- New length of path P is  $\ell(P) + \alpha |P|$ , so original shortest path might no longer be shortest path if it has many edges.



Some other kind of reweighting? Need new lengths  $\hat{\ell}$  such that:

- **P** Path  $m{P}$  a shortest path under lengths  $\ell$  if and only  $m{P}$  a shortest path under lengths  $\hat{\ell}$
- ▶  $\hat{\ell}(u,v) \ge 0$  for all  $(u,v) \in E$

Jessica Sorrell Lecture 17: APSP October 28, 2025 11 / 14

## Vertex Reweighting

Neat observation: put weights at vertices!

- ▶ Let  $h: V \to \mathbb{R}$  be node weights.

Neat observation: put weights at vertices!

- ▶ Let  $h: V \to \mathbb{R}$  be node weights.

Let  $P = (v_0, v_1, \dots, v_k)$  be arbitrary (not necessarily shortest) path.

 Jessica Sorrell
 Lecture 17: APSP
 October 28, 2025
 12 / 14

Neat observation: put weights at vertices!

- ▶ Let  $h: V \to \mathbb{R}$  be node weights.

Let  $P = (v_0, v_1, \dots, v_k)$  be arbitrary (not necessarily shortest) path.

$$\ell_h(P) = \sum_{i=0}^{k-1} \ell_h(v_i, v_{i+1}) = \sum_{i=0}^{k-1} (\ell(v_i, v_{i+1}) + h(v_i) - h(v_{i+1}))$$

Neat observation: put weights at vertices!

- ▶ Let  $h: V \to \mathbb{R}$  be node weights.

Let  $P = (v_0, v_1, \dots, v_k)$  be arbitrary (not necessarily shortest) path.

$$\ell_h(P) = \sum_{i=0}^{k-1} \ell_h(v_i, v_{i+1}) = \sum_{i=0}^{k-1} (\ell(v_i, v_{i+1}) + h(v_i) - h(v_{i+1}))$$

$$= h(v_0) - h(v_k) + \sum_{i=0}^{k-1} \ell(v_i, v_{i+1})$$
 (telescoping)

Neat observation: put weights at vertices!

- ▶ Let  $h: V \to \mathbb{R}$  be node weights.
- Let  $\ell_h(u,v) = \ell(u,v) + h(u) h(v)$

Let  $P = (v_0, v_1, \dots, v_k)$  be arbitrary (not necessarily shortest) path.

$$\ell_h(P) = \sum_{i=0}^{k-1} \ell_h(v_i, v_{i+1}) = \sum_{i=0}^{k-1} (\ell(v_i, v_{i+1}) + h(v_i) - h(v_{i+1}))$$

$$= h(v_0) - h(v_k) + \sum_{i=0}^{k-1} \ell(v_i, v_{i+1})$$

$$= \ell(P) + h(v_0) - h(v_k)$$
(telescoping)

Neat observation: put weights at vertices!

- ▶ Let  $h: V \to \mathbb{R}$  be node weights.
- Let  $\ell_h(u,v) = \ell(u,v) + h(u) h(v)$

Let  $P = (v_0, v_1, \dots, v_k)$  be arbitrary (not necessarily shortest) path.

$$\ell_h(P) = \sum_{i=0}^{k-1} \ell_h(v_i, v_{i+1}) = \sum_{i=0}^{k-1} (\ell(v_i, v_{i+1}) + h(v_i) - h(v_{i+1}))$$

$$= h(v_0) - h(v_k) + \sum_{i=0}^{k-1} \ell(v_i, v_{i+1})$$

$$= \ell(P) + h(v_0) - h(v_k)$$
 (telescoping)

 $h(v_0) - h(v_k)$  added to every  $v_0 \rightarrow v_k$  path, so shortest path from  $v_0$  to  $v_k$  still shortest path!

So vertex reweighting preserves shortest paths. Find weights to make lengths nonnegative?

Add new node s to graph, edges (s, v) for all  $v \in V$  of length 0

So vertex reweighting preserves shortest paths. Find weights to make lengths nonnegative?

Add new node s to graph, edges (s, v) for all  $v \in V$  of length 0

- ▶ Run Bellman-Ford from s, then for all  $u \in V$  set h(u) to be d(s, u)
- ▶ Note  $h(u) \le 0$  for all  $u \in V$

So vertex reweighting preserves shortest paths. Find weights to make lengths nonnegative?

Add new node s to graph, edges (s, v) for all  $v \in V$  of length 0

- ▶ Run Bellman-Ford from s, then for all  $u \in V$  set h(u) to be d(s, u)
- ▶ Note  $h(u) \le 0$  for all  $u \in V$

Want to show that  $\ell_h(u, v) \ge 0$  for all edges (u, v).

► Triangle inequality:  $h(v) = d(s, v) \le d(s, u) + \ell(u, v) = h(u) + \ell(u, v)$ 

So vertex reweighting preserves shortest paths. Find weights to make lengths nonnegative?

Add new node s to graph, edges (s, v) for all  $v \in V$  of length 0

- ▶ Run Bellman-Ford from s, then for all  $u \in V$  set h(u) to be d(s,u)
- ▶ Note  $h(u) \le 0$  for all  $u \in V$

Want to show that  $\ell_h(u, v) \ge 0$  for all edges (u, v).

► Triangle inequality:  $h(v) = d(s, v) \le d(s, u) + \ell(u, v) = h(u) + \ell(u, v)$ 

$$\ell_h(u,v) = \ell(u,v) + h(u) - h(v) \ge \ell(u,v) + h(u) - (h(u) + \ell(u,v)) = 0$$

### Johnson's Algorithm

- Add vertex **s** to graph, edge (s, u) for all  $u \in V$  with  $\ell(s, u) = 0$
- Run Bellman-Ford from s, set h(u) = d(s, u)
- ▶ Remove s, run Dijkstra from every node  $u \in V$  to get  $d_h(u, v)$  for all  $u, v \in V$
- ▶ If want distances, set  $d(u, v) = d_h(u, v) h(u) + h(v)$  for all  $u, v \in V$

Correctness: From previous discussion.

# Johnson's Algorithm

- Add vertex s to graph, edge (s, u) for all  $u \in V$  with  $\ell(s, u) = 0$
- ▶ Run Bellman-Ford from s, set h(u) = d(s, u)
- ▶ Remove s, run Dijkstra from every node  $u \in V$  to get  $d_h(u, v)$  for all  $u, v \in V$
- ▶ If want distances, set  $d(u, v) = d_h(u, v) h(u) + h(v)$  for all  $u, v \in V$

Correctness: From previous discussion.

#### **Running Time:**

# Johnson's Algorithm

- Add vertex s to graph, edge (s, u) for all  $u \in V$  with  $\ell(s, u) = 0$
- ▶ Run Bellman-Ford from s, set h(u) = d(s, u)
- ▶ Remove s, run Dijkstra from every node  $u \in V$  to get  $d_h(u, v)$  for all  $u, v \in V$
- ▶ If want distances, set  $d(u, v) = d_h(u, v) h(u) + h(v)$  for all  $u, v \in V$

Correctness: From previous discussion.

Running Time:  $O(n) + O(mn) + O(n(m+n\log n)) = O(mn+n^2\log n)$